

AGRO M-10DM

SEASONAL MOTOR OIL FOR DIESEL ENGINES.

SPECIFICATIONS:

SAE 30 API CD

DESCRIPTION:

It is Intended for lubrication of high-powered turbocharged diesel engines operating in severe conditions (trucks of the MAZ type, road trains, tractors, city and intercity buses, quarry dump trucks, bulldozers, heavy industrial tractors), and medium-powered moderately supercharged or non-supercharged diesels with increased mileage between oil changes.

It is produced from mineral base oils with high-quality additives.

BENEFITS:

• A large reserve of alkalinity provides an excellent washing and neutralizing ability of the oil during the entire period of operation;

- Increased anti-wear and anti-corrosion properties;
- It has high thermal stability;
- It is characterized by resistance to foaming, guarantees excellent lubrication of parts;
- Ensures long mileage between oil changes.

Kinematic viscosity at 100 °C, mm²/s 12.4		
Density at 20°C, kg/m ³	892	
Viscosity index, min	91	
TBN mg KOH/g	8.5	
Flash point in open crucible, $^\circ C$, min		
Pour point, °C	-18	

TYPICAL CHARACTERISTICS:

Packing	Vendor code	Barcode
Barrel metal 200l	024147	482007024035
Canister plastic 20I	024141	482007024034
Oilbox carton polyethylene 20l	018312	482007024672
Canister plastic 5l	001049	482007024200

Выпускается по ГОСТ 8581-78. Данная информация является справочной и может быть изменена без уведомления. Данная публикация от 01.09.2014 г. заменяет все раннее опубликованные описания данного продукта.

