

ANTIFREEZE -40 (SUPER G12+ RED)

HIGH-QUALITY COOLANT LIQUID.

SPECIFICATIONS:

ASTM D3306

ASTM D4985

DESCRIPTION:

High-quality coolant liquid for modern gasoline and diesel engines (including engines made of light metals), which are operated in a variety of seasonal and climatic conditions.

YUKO Antifreeze Super G12+ is especially recommended for cooling systems made of aluminum. Provides reliable protection of the engine parts made of iron, aluminum, copper and steel. Made on monoethylene glycol and special anti-corrosion additives basis, produced by BASF.

Does not contain nitrites, amines, silicates, borates and phosphates.

Without glycerine.

APPROVAL:

G12+

CONFORMITY:

Audi/Seat/Skoda/VW TL 774-D/F (G12)

MB 325.3

MAN 324 SNF

Ford WSS-M 97B44-D

MTU MTL 5048

Porsche

Scania TI 02-98 0813 T/B/M sv

BENEFITS:

- Highly efficient and long lasting corrosion protection for all cooling system components, especially aluminum made ones;
- Maintenance-free freezing and overheating protection;
- Increased refrigerant strength;
- Non-aggressive to lacquer, flexible tubes and seals;
- Corresponds to the best world G12 class liquids analogues;
- May be mixed with G12 class liquids.

TYPICAL CHARACTERISTICS:

| | |
|--|---------------|
| Density at 20°C, g/cm ³ | 1,040 – 1,100 |
| Corrosive effect on metals | withstands |
| Copper, brass, steel, cast, iron, aluminum | 0,2 |
| Solder | 0,3 |
| Hydrogen index (pH), at 20°C | 7,5-11 |
| Alcalinity, cm ³ , min | 2 |
| Foam formation, cm ³ , max | 30 |
| Crystallization start temperature, °C | -38 |
| Color | red |

| Packing | Vendor code | Barcode |
|-----------------------|-------------|--------------|
| Canister plastic 10kg | 019943 | 482007024823 |
| Barrel metal 200l | 017740 | 482007024807 |
| Canister plastic 20l | 017541 | 482007024896 |
| Canister plastic 1kg | 015218 | 482007024448 |
| Canister plastic 5l | 014031 | 482007024822 |