

## MEGA DIESEL 10W-40

**SEMI-SYNTHETIC ALL-SEASON MOTOR OIL FOR MODERN DIESEL ENGINES.**

### SPECIFICATIONS:

SAE 10W-40

API CI-4

API SL

ACEA E7

### DESCRIPTION:

The newest all-season semi-synthetic motor oil for long-distance and urban trucks, agricultural and construction machinery, buses and other commercial vehicles.

Produced of high-quality base oils with high-efficient modern additives package. Provides high antifriction, anticorrosion, detergent and antioxidizing oil properties throughout the service life.

Intended for year-round use incl. modern high-speed air and turbo diesel engines.

### APPROVAL:

MB 228.3

Volvo VDS-3

CAT-ECF-1

CES 20078

### CONFORMITY:

MB 228.3

MAN M3275-1

Volvo VDS-3

Renault RLD-2

CES 20076/77

MTU Type 2

ECF-1a

DQC III-10

## BENEFITS:

- Easy cold start in winter;
- Consistently high performance in various operating modes throughout the service life;
- Prevents high and low temperature deposits formation in the engine;
- Improved anti-foam properties, that significantly reduces foaming in the hydraulic drive system of the valves;
- Compatible with all engine sealings;
- High-class performance properties allow to apply Yuko Mega Diesel 10W-40 in the engines of most modern commercial vehicles.

## TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	14.8
Density at 20°C, kg/m <sup>3</sup>	875
Viscosity index	150
Alkalinity, mg KOH/g	9,1
Flash point in open crucible, °C	222
Pour point, °C	-32

Packing	Vendor code	Barcode
Canister plastic 20l	021325	4820070240511
Barrel metal 200l	005274	482007024053

**0 800 60 5555**

Telephone hotline