

# CIATIM-201

## SPECIAL FROST-RESISTANT AND REFRACTORY GREASE.

## **SPECIFICATIONS:**

NLGI 2

## **DESCRIPTION:**

It is intended for lubrication of friction nodes of precise mechanisms in aviation, electromechanical and other engineering.

TSIATIM-201 grease is operational for a long time in the temperature range from -60  $^{\circ}$ C to +90  $^{\circ}$ C. In terms of low-temperature characteristics, TSIATIM-201 lubricant is one of the best in Ukraine.

#### **BENEFITS:**

### • Excellent low-temperature characteristics;

- Lubricant does not solidify under the influence of elevated temperatures or during storage;
- The possibility of using lubricant in friction nodes of all types;
- It has refractory properties;
- Warranty period of storage is 5 years.

| Packing         | Vendor code | Barcode      |
|-----------------|-------------|--------------|
| Bucket tin 17kg | 001349      | 482007024152 |
| Tin can 800g    | 009914      | 482007024151 |

## **TYPICAL CHARACTERISTICS:**

| Efficient viscosity at -20 °C, Pa • s-1, no more 1000 |      |  |
|---|------|--|
| Tensile strength at 20°C, Pa                          | 500  |  |
| Dropping point, °C                                    | 196  |  |
| Colloid stability,%, not more                         | 22.8 |  |
| Penetration, mm • 10 -1                               | 215  |  |