

YUKO UTTO 80W

UNIVERSAL TRACTOR OIL FOR HYDRAULIC SYSTEMS AND TRANSMISSIONS

SPECIFICATIONS:

API CI-4

DESCRIPTION:

Universal UTTO-type tractor oil is designed for gearboxes, main gears, hydraulic systems lubrication, as well as wet brakes and clutches in tractors, forestry and agricultural machinery and construction machines. It is also used for heavy operating conditions.

YUKO AGRO UTTO produced using high quality mineral base oils and a multifunctional additive package.

CONFORMITY:

JOHN DEERE J20A, J20C

AGCO MF M1135, M1139, M1141

CASE MS1207, MS1210

ZF TE-ML 03E, 05F, 06D, 06K, 06M, 06N, 06R, 17E, 21F

ALLISON C4

Caterpillar TO-2

Case New Holland MAT-3525

M2C-134 A-D

FNHA-2-D.201.00

Volvo WB 101

Massey-Ferguson M1143 M1145

Ford

BENEFITS:

- Excellent anti-wear properties ensure maximum service life of machine parts;
- Application of friction modifiers allows to achieve the necessary level of frictional properties, ensuring efficient operation of wet brakes and clutch;
- Excellent anti-wear and extreme pressure properties ensure the protection of gears and hydraulic systems in a wide range of temperatures;
- Can be used as a general lubricant for the transmission and hydraulic system;
- Reliable protection of tractor units in various operating conditions.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	9,7
Viscosity index	138
Alkalinity TBN, mg KOH/g	9.2
Flash point in open crucible, °C	220
Pour point, °C	-30

Packing	Vendor code	Barcode
Barrel metal 200l	011118	
Bucket tin 20l	011335	
In bulk	000000	