

# ANTIFREEZE -32 (SUPER G11 BLUE)

HIGH-QUALITY COOLANT LIQUID.

## SPECIFICATIONS:

ASTM D3306

ASTM D4985

## DESCRIPTION:

High-quality coolant liquid for modern gasoline and diesel engines (including engines made of light metals) which are operated in a variety of seasonal and climatic conditions.

YUKO Antifreeze Super G11 will protect your engine from freezing, overheating, corrosion and damaging deposits.

Provides reliable protection of the engine parts made of iron, aluminum, copper and steel. Made on monoethylene glycol and special anti-corrosion additives basis, produced by BASF. Does not contain nitrites, amines, silicates, borates and phosphates.

Without glycerine.

## APPROVAL:

G11

## CONFORMITY:

VW/Audi/Seat/Skoda TL 774-C (G 11)

BMW GS 9400

MAN 324 NF

MB 325.0/325.2

MTU (MTL 5048)

BS 6580

Porsche

Saab 6901 599

Opel GM QL 130100

Cummins 85T8-2

Cummins CES 14603

Caterpillar

Detroit Diesel 7SE298

John Deere 8650-5

Case

New Holland

Volvo

MACK 014617004

## BENEFITS:

- Excellent corrosion protection;
- Reduces possible cavitation damage for example damage of cooling liquid pump;
- Prevents foaming and compatible with rubber seals;
- Freezing and overheating protection due to high boiling point. Increased refrigerant strength;
- Corresponds to the best world G11 class liquids analogues.

## TYPICAL CHARACTERISTICS:

Density at 20°C, g/cm <sup>3</sup>	1,040 – 1,100
Corrosive effect on metals	withstands
Copper, brass, steel, cast, iron, aluminum	0,2
Solder	0,3
Hydrogen index (pH), at 20°C	7,5-11
Alcalinity, cm <sup>3</sup> , min	2
Foam formation, cm <sup>3</sup> , max	30
Crystallization start temperature, °C	-38
Color	blue

Packing	Vendor code	Barcode
Canister plastic 5l	023721	
Canister plastic 1kg	023717	