

# ANTIFREEZE -32 (SUPER G12+ RED)

HIGH-QUALITY COOLANT LIQUID.

## SPECIFICATIONS:

ASTM D3306

ASTM D4985

## DESCRIPTION:

High-quality coolant liquid for modern gasoline and diesel engines (including engines made of light metals), which are operated in a variety of seasonal and climatic conditions.

YUKO Antifreeze Super G12+ is especially recommended for cooling systems made of aluminum. Provides reliable protection of the engine parts made of iron, aluminum, copper and steel. Made on monoethylene glycol and special anti-corrosion additives basis, produced by BASF.

Does not contain nitrites, amines, silicates, borates and phosphates.

**Without glycerine.**

## APPROVAL:

G12+

## CONFORMITY:

Audi/Seat/Skoda/VW TL 774-D/F (G12)

MB 325.3

MAN 324 SNF

Ford WSS-M 97B44-D

MTU MTL 5048

Porsche

Scania TI 02-98 0813 T/B/M sv

## BENEFITS:

- Highly efficient and long lasting corrosion protection for all cooling system components, especially aluminum made ones;
- Maintenance-free freezing and overheating protection;
- Increased refrigerant strength;
- Non-aggressive to lacquer, flexible tubes and seals;
- Corresponds to the best world G12 class liquids analogues;
- May be mixed with G12 class liquids.

## TYPICAL CHARACTERISTICS:

Density at 20°C, g/cm <sup>3</sup>	1,040 – 1,100
Corrosive effect on metals	withstands
Copper, brass, steel, cast, iron, aluminum	0,2
Solder	0,3
Hydrogen index (pH), at 20°C	7,5-11
Alcalinity, cm <sup>3</sup> , min	2
Foam formation, cm <sup>3</sup> , max	30
Crystallization start temperature, °C	-38
Color	red

Packing	Vendor code	Barcode
Canister plastic 5l	023722	
Canister plastic 1kg	023718	