

# ANTIFREEZE CONCENTRATE (SUPER G11 BLUE)

## HIGH-QUALITY CONCENTRATE COOLANT

### SPECIFICATIONS:

ASTM D3306

ASTM D4985

### DESCRIPTION:

High-quality concentrate coolant for modern gas and diesel engines of cars, trucks, agricultural machinery, stationary engines (including engines of light metals), which operated in all seasonal and climatic conditions.

Yuko Antifreeze Concentrate (Super G11 blue) - produced on the basis of monoethylene glycol and special anti-corrosion additives. Does not contain glycerol, nitrites, amines, silicates, phosphates and borates.

Yuko Antifreeze Concentrate (Super G11 blue) should be mixed before pouring into the cooling circuit with water at a concentration of 33 to max. 60 vol% can be used. Applying a 50/50 ratio for the mixture of water and concentrate is recommended.

Protection against the cold / antifreeze

50 vol% in water -38 °C

33 vol% in water -18 °C

### APPROVAL:

G11

### CONFORMITY:

VW/Audi/Seat/Skoda TL 774-C (G 11)

BMW GS 9400

MAN 324 NF

MB 325.0/325.2

MTU (MTL 5048)

BS 6580

Porsche

Saab 6901 599

Opel GM QL 130100

Cummins 85T8-2

Cummins CES 14603

Caterpillar

Detroit Diesel 7SE298

John Deere 8650-5

Case

New Holland

Volvo

MACK 014617004

## BENEFITS:

- Powerful and long-lasting protection against corrosion for all parts of the cooling system, which consist of materials such as steel, cast iron, aluminum, copper, brass, soft solder
- Extended coolant life
- Maintenance-free frost and overheating protection
- Avoidance of sediments, which can cause radiator plugging
- Avoidance of foaming

## TYPICAL CHARACTERISTICS:

Relative density at 15.6 °C	1118 kg/m <sup>3</sup>
pH value 50% vol aqueous solution	8.4
Freezing point	-42 °C
Colour	blue

Packing	Vendor code	Barcode
Barrel metal 200l	018442	482007024924
Canister plastic 10kg	019359	

**0 800 60 5555**

Telephone hotline