

# ANTIFREEZE CONCENTRATE (SUPER G12+ RED)

## HIGH-QUALITY CONCENTRATE COOLANT

### DESCRIPTION:

High-quality concentrate coolant for modern, powerful and heavy duty gas and diesel engines of cars, trucks, agricultural machinery, stationary engines, which operated in a variety of seasonal and climatic conditions. Especially recommended for use in engine cooling systems made of aluminium.

Protects engine against freezing, overheating, corrosion, prevents the formation of harmful deposits. It provides reliable protection of the engine metal parts made of cast iron, aluminium, copper and steel.

Antifreeze Concentrate (Super G12+ red) produced on the basis of monoethylene glycol and special anti-corrosion additives. Does not contain glycerol, nitrites, amines, silicates, phosphates and borates.

### Application:

Recommended working concentration 50 % Antifreeze Concentrate (Super G12+ red) and 50% water, radiator protection up to -38 °C can be achieved.

Antifreeze protection down to -68°C is possible with a maximum of 69% Antifreeze Concentrate (Super G12+ red) and 31% water.

### APPROVAL:

G12+

### CONFORMITY:

Audi/Seat/Skoda/VW TL 774-D/F (G12)

MB 325.3

MAN 324 SNF

Ford WSS-M 97B44-D

MTU MTL 5048

Porsche

Scania TI 02-98 0813 T/B/M sv

## BENEFITS:

- Longer and outstanding corrosion protection
- Improved heat transfer
- Suitable for mixed fleets, one product for cars, trucks and construction machinery
- Ecologically desirable because of longer working life
- Avoidance of foaming

## TYPICAL CHARACTERISTICS:

Relative density at 15.6 °C	1119 kg/m <sup>3</sup>
pH value 50% vol aqueous solution	8.7
Freezing point	-42 °C
Colour	red

Packing	Vendor code	Barcode
Barrel metal 200l	018991	482311040050
Canister plastic 10kg	019350	

**0 800 60 5555**

Telephone hotline