

EXTRA SYNT 0W-16

SYNTHETIC MOTOR OIL.

SPECIFICATIONS:

SAE 0W-16

API SP

ILSAC GF-6B

DESCRIPTION:

High-performance fully synthetic engine oil especially developed for American and Asian petrol engines of passenger cars, delivery vans and hybrids. Minimizes the risk of Low Speed Pre-Ignition in modern engines with GDI and TGDI. Ensures excellent low temperature flow characteristics to provide optimum protection for the engine at the cold start phase. Withstands extreme loads and safely handles high temperatures under all operating conditions.

CONFORMITY:

Ford

GM

Chrysler

Toyota

Lexus

KIA

Honda

Nissan

Mitsubishi

Subaru

Suzuki

BENEFITS:

- Ensures a stable lubricating film over a wide temperature range;
- Reduction of fuel consumption and car exhaust emissions
- Excellent mechanical High Temperature High Shear (HTHS) rate stability throughout the entire service life.

TYPICAL CHARACTERISTICS:

 Viscosity mm²/s at 100 °C 7,7

 Density at 20°C, kg/m³ 858

Viscosity Index 159

Pour point °C -50

Flash point in open crucible, °C 225

Packing

Vendor code

Barcode

Canister plastic 5l

021175