

FULLY SYNTHETIC 10W-30

SYNTHETIC MOTOR OIL.

SPECIFICATIONS:

SAE 10W-30

API SN

API CF

ACEA A3/B4

DESCRIPTION:

Performance fully synthetic engine oil of high-tech grade. Developed for the latest gas and diesel engines of passenger cars and buses. Compatible with injector and multivalve engines including those turbocharged and equipped with intercooler and catalyzer.

Essentially extends the engine life due to multifunction additives which provide advanced low-temperature, antiwear, anticorrosion, detergent and antioxidant properties. Best for use in urban conditions. Ensures low fuel consumption. Meets the requirements of the majority of Japanese, Korean and American passenger car manufacturers (A&A).

CONFORMITY:

Toyota

Honda

Ford

VW 502.0

VW 505.00/505.01

BM 229.31

Opel

GM-LL-025

Renault RN0700

Renault RN0710

BENEFITS:

- Provides a reliable engine protection under various conditions incl. extreme operating mode;
- Optimum for the use both in urban cycle and cross-country conditions;
- Due to its fluidity reduces fuel consumption;
- Significantly extends engine service life due to multipurpose additives package, with excellent low temperature, antifriction, anticorrosion, detergent and antioxidant properties;
- Maintains effectiveness for maximum long period, which allows to extend significantly oil drain intervals;
- Due to superior viscosity/temperature properties, provides safe engine start at low temperatures in winter, including the regions with harsh weather conditions in winter;
- Conforms to modern requirements of world leaders in equipment manufacture concerning oil consumption, volatility, energy saving.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	9,3 – 12,5
Density at 20°C, kg/m ³	900
Viscosity index	115
TBN mg KOH/g	9,0
Flash point in open crucible, °C	200
Pour point, °C	-30

Packing	Vendor code	Barcode
Canister plastic 5l	018865	
Barrel metal 200l	022343	4823110402511