

MAX SYNTHETIC 0W-20

SYNTHETIC MOTOR OIL.

SPECIFICATIONS:

SAE 0W-20

API SP

ILSAC GF-6A

DESCRIPTION:

High performance, fuel-efficient synthetic engine oil for the latest gasoline and diesel engines, equipped with the modern exhaust gas aftertreatment systems. Contains PAO. Designed for vehicles, manufactured for the American and Asian markets (A&A).

Ideal for extended drain intervals (Longlife).

Approved for dynamic and extreme driving styles.

CONFORMITY:

GM dexos1 Gen 2

Ford WSS-M2C947-A, WSS-M2C962-A1

Chrysler MS-6395

FIAT 9.55535-CR1/GSX

Toyota

Nissan

Honda/Acura

Mitsubishi

Mazda

Suzuki

HYBRID Cars

Honda/Acura HTO-6

GM 6094 M

MB 229.6

BMW LL-01 FE

Ford WSS-M2C947-A

VOLVO 95200377

STJLR 03.5003

BENEFITS:

- Ensures a stable lubricating film over a wide temperature range;
- Reduction of fuel consumption and car exhaust emissions
- Excellent mechanical High Temperature High Shear (HTHS) rate stability throughout the entire service life.

TYPICAL CHARACTERISTICS:

 Viscosity mm²/s at 100 °C 7,7

 Density at 20°C, kg/m³ 858

Viscosity Index 159

Pour point °C -50

Flash point in open crucible, °C 225

Packing	Vendor code	Barcode
Canister plastic 5l	020683	
Canister plastic 5l	020153	
Canister plastic 1l	020149	