

MAX SYNTHETIC 0W-20

SYNTHETIC MOTOR OIL.

SPECIFICATIONS:

SAE 0W-20

API SP

ILSAC GF-6A

DESCRIPTION:

High performance, fuel-efficient synthetic engine oil for the latest gasoline and diesel engines, equipped with the modern exhaust gas aftertreatment systems. Designed for vehicles, manufactured for the American and Asian markets (A&A).

Ideal for extended drain intervals (Longlife).

Approved for dynamic and extreme driving styles.

CONFORMITY:

GM dexos1 Gen 2

Ford WSS-M2C947-A, WSS-M2C962-A1

Chrysler MS-6395

FIAT 9.55535-CR1/GSX

Toyota

Nissan

Honda/Acura

Mitsubishi

Mazda

Suzuki

HYBRID Cars

Honda/Acura HTO-6

GM 6094 M

MB 229.6

BMW LL-01 FE

VOLVO 95200377

STJLR 03.5003

BENEFITS:

- Ensures a stable lubricating film over a wide temperature range;
- Reduction of fuel consumption and car exhaust emissions
- Excellent mechanical High Temperature High Shear (HTHS) rate stability throughout the entire service life.

TYPICAL CHARACTERISTICS:

Viscosity mm ² /s at 100 °C	7,7
Density at 20°C, kg/m ³	840
Viscosity Index	177
Flash point in open crucible, °C	225
Pour point °C	-44

Packing	Vendor code	Barcode
Tin can 4l	022063	4820070241521
Tin can 1l	021555	