

MAX SYNTHETIC 5W-30

SYNTHETIC MOTOR OIL.

SPECIFICATIONS:

SAE 5W-30

API SP

ILSAC GF-6A

DESCRIPTION:

High performance, fuel-efficient synthetic engine oil for the latest gasoline and diesel engines, equipped with the modern exhaust gas aftertreatment systems. Contains PAO. Designed for vehicles, manufactured for the American and Asian markets (A&A).

Ideal for extended drain intervals (Longlife).

Approved for dynamic and extreme driving styles.

CONFORMITY:

GM dexos1 Gen 2

GM 6094M/4718M

Ford WSS-M2C929-A/946A, WSS-M2C945-A

Renault RN0700

Toyota

Nissan

Honda/Acura

Mitsubishi

Mazda

Suzuki

Chrysler MS 6395

Ford WSS M2C 912A/913A/B/C/D

Jaguar

Land Rover STJLR.03.5003

BENEFITS:

- Ensures a stable lubricating film over a wide temperature range;
- Reduction of fuel consumption and car exhaust emissions
- Excellent mechanical High Temperature High Shear (HTHS) rate stability throughout the entire service life.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	10.2
Density at 20°C, kg/m ³	855
Viscosity Index	175
Flash point in open crucible, °C	215
Pour point °C	-42

Packing	Vendor code	Barcode
Tin can 1l	021577	
Tin can 4l	022065	482311040152
Oilbox carton polyethylene 20l	020773	