

MAX SYNTHETIC A&A 10W-30

FUEL-ECONOMY FULLY SYNTHETIC MOTOR OIL

SPECIFICATIONS:

SAE 10W-30

API SP

ILSAC GF-6A

DESCRIPTION:

High performance, fuel-efficient synthetic engine oil for the latest gasoline and diesel engines, equipped with the modern exhaust gas aftertreatment systems. Contains PAO.

Designed for vehicles, manufactured for the American and Asian markets (A&A).

Ideal for extended drain intervals (Longlife). Approved for dynamic and extreme driving styles.

CONFORMITY:

GM dexos1 Gen 2

Ford WSS-M2C929-A

Ford WSS-M2C946-A

Ford WSS-M2C945-A

Chrysler MS-6395

Nissan

Honda/Acura

Mitsubishi

Mazda

Toyota

Suzuki

BENEFITS:

- Ensures a stable lubricating film over a wide temperature range;
- Reduction of fuel consumption and car exhaust emissions

TYPICAL CHARACTERISTICS:

 Viscosity mm²/s at 100 °C 9.3-12.5

 Density at 20°C, kg/m³ 910

Viscosity Index 135

Pour point °C -33

Flash point in open crucible, °C 200

Packing	Vendor code	Barcode
Canister plastic 4l	023042	
Canister plastic 1l	022735	