

# **MEGA DIESEL 10W-40**

## SEMI-SYNTHETIC ALL-SEASON MOTOR OIL FOR MODERN DIESEL ENGINES.

## **SPECIFICATIONS:**

SAE 10W-40 API CI-4 API SL ACEA E7

# **DESCRIPTION:**

The newest all-season semi-synthetic motor oil for long-distance and urban trucks, agricultural and construction machinery, buses and other commercial vehicles.

Produced of high-quality base oils with high-efficient modern additives package. Provides high antifriction, anticorrosion, detergent and antioxidizing oil properties throughout the service life.

Intended for year-round use incl. modern high-speed air and turbo diesel engines.

#### **APROVAL:**

MB 228.3 Volvo VDS-3 CAT-ECF-1 CES 20078

#### **CONFORMITY:**

MB 228.3 MAN M3275-1 Volvo VDS-3 Renault RLD-2 CES 20076/77 MTU Type 2 ECF-1a

DQC III-10

### **BENEFITS:**

- Easy cold start in winter;
- Consistently high performance in various operating modes throughout the service life;
- Prevents high and low temperature deposits formation in the engine;
- Improved anti-foam properties, that significantly reduces foaming in the hydraulic drive system of the valves:
- Compatible with all engine sealings;
- High-class performance properties allow to apply Yuko Mega Diesel 10W-40 in the engines of most modern commercial vehicles.

Packing	Vendor code	Barcode
Canister plastic 20l	021325	4820070240511
Barrel metal 2001	005274	482007024053

### **TYPICAL CHARACTERISTICS:**

Kinematic viscosity at 100°C, mm²/s 14.8		
Density at 20°C, kg/m³	855	
Viscosity index	168	
Alkalinity, mg KOH/g	9,3	
Flash point in open crucible, °C	222	
Pour point, °C	-44	