

# RACING SYNT 10W-60

**SYNTHETIC MOTOR OIL FOR MODERN GASOLINE ENGINES OF RACING CARS.**

## SPECIFICATIONS:

SAE 10W-60

API SN

API CF

ACEA A3/B4

## DESCRIPTION:

Fully synthetic engine oil specially formulated for high performance boosted engines. PAO (polyalphaolefins) basis formulation provides optimum wear protection and lubrication at extreme loads. The high viscosity index maintains the most stable pressure in the lubrication system at various temperatures. Optimal for the use of highly accelerated engines of production cars as well as in specially customized sport racing cars.

## BENEFITS:

- Wide range of operating temperatures.
- Stable operation in high-load engines.
- Reliable motor protection even in extreme operating conditions.

## TYPICAL CHARACTERISTICS:

|  |      |
|--|------|
| Kinematic viscosity at 100°C, mm <sup>2</sup> /s | 23,5 |
| Density at 20°C, kg/m <sup>3</sup>               | 875  |
| Viscosity Index                                  | 165  |
| Flash point in open crucible, °C                 | 215  |
| Pour point °C                                    | -30  |

| Packing                        | Vendor code | Barcode |
|--------------------------------|-------------|---------|
| Oilbox carton polyethylene 20l | 019955      |         |
| Canister plastic 5l            | 019952      |         |