

REDUS MOLYBDENUM

GEAR GREASE WITH MOLYBDENUM

SPECIFICATIONS:

NLGI 2

DIN 51502: KPF2K-40

DESCRIPTION:

Molybdenum disulphide (MoS_2) water-resistant anti-wear lubricant for lawn and garden equipment gearboxes: lawn mowers, brush cutters, trimmers, electric shears, garden vacuum cleaners and blowers, drive elements of cultivators, snowblowers and other equipment that works in vibration, extremely high and shock loads. It is also used to lubricate the moving parts of gearboxes, crosses, cardan joints of power tools.

Based on lithium hydroxystearate, fortified with extreme pressure, anti-oxidation and anti-friction additives.

For the convenience of applying lubricant, the tube is equipped with a removable nose-applicator.

BENEFITS:

- High anti-wear and extreme pressure characteristics;
- Great for high-speed equipment nodes;
- Mechanical and antioxidant stability;
- Low evaporation and good water resistance;
- Reliable lubrication and protection against overheating;
- Wide temperature range of application.

TYPICAL CHARACTERISTICS:

Efficient viscosity at -20 °C, Pa • s-1, not more then	1200
Penetration at 25°C, mm•10-1	260
Dropping Point, °C	195
Corrosion impact	stands
Colloid stability, %	16
Evaporation, not more then	3
Mechanical admixture, %, not more then	0,0025
Welding load, N, min	3685
Water content, %, max	0,03

Packing	Vendor code	Barcode
Tuba plastic 0.125l	015182	482007024402