

## SHRUS-4 (NLGI2,EP2)

### AUTOMOTIVE GREASE WITH MOLYBDENUM DISULPHIDE.

#### SPECIFICATIONS:

NLGI 2

#### DESCRIPTION:

Used for lubrication of constant velocity joints (SHRUS) in front-driven and all-wheel drive cars. Used for lubrication of ball double row bearings as well, which are used in wheel sets of domestic and imported cars.

The grease is produced based on Lithium hydroxystearate, improved with extreme pressure, anti-oxidizing and antifriction additive.

#### BENEFITS:

- Superior anti-wear and extreme pressure properties;
- Good water resistance;
- High mechanical and oxidation stability;
- Low volatility;
- Extends regular lubrication period;
- Wide temperature range of application.

#### TYPICAL CHARACTERISTICS:

Dropping point, °C	195
Penetration, mm • 10 <sup>-1</sup>	260
Tensile strength at 20°C, Pa	620
Colloid stability, %, not more	10
Evaporation, %, not more	4,8
Tribological Characteristics on a 4-ball machine, N, not less than	
- Scuff index, N	560
- Welding load, N	4900
- Critical load, N	1568

Packing	Vendor code	Barcode
Doi-pack plastic 0.375l	004916	482007024144