

SUPER DIESEL 10W-40

ALL-SEASON MINERAL MOTOR OIL FOR MODERN DIESEL ENGINES.

SPECIFICATIONS:

SAE 10W-40

API CF-4

API SJ

ACEA E2

ACEA E5

DESCRIPTION:

Intended for diesel engines of passenger cars, vans and trucks incl. powered by fuel with high sulphur content.

Produced of mineral base oils with modern additives, providing oil performance stability throughout the whole service and shelf life.

CONFORMITY:

MB 228.1

MAN M271

Volvo VDS/VDS-2

BENEFITS:

- Excellent lubricating, detergent and anticorrosive properties
- Prevents high and low temperature deposits formation in the engine
- It is optimum for the most common diesel engine models
- Compatible with all engine sealings
- A wide range of packaging meets the requirements of any equipment

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	13,5-15,5
Density at 20°C, kg/m ³	910
Viscosity index	120
Alkalinity, mg KOH/g	9,0
Flash point in open crucible, °C	200
Pour point, °C	-30

Packing	Vendor code	Barcode
Barrel metal 200l	018082	482007024640
Bucket tin 20l	018081	482007024639

Produced according to TU U 23.2-31852954-008-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.

0 800 60 5555

Telephone hotline