

SUPER GAS 10W-40

SEMI-SYNTHETIC ENGINE OIL FOR CARS EQUIPPED WITH LPG

SPECIFICATIONS:

SAE 10W-40

API SM

API CF

DESCRIPTION:

Premium quality semy-synthetic motor oil intended for modern gasoline and diesel engines operating on natural gas (LPG - a mixture of propane and butane or CNG - methane) of passenger cars, vans and light trucks.

Produced from high quality base oils using a unique synthetic components that provides viscosity grade SAE 10W-40.

Compatible with injector engines, including turbocharged with intercooler and catalyst.

BENEFITS:

- High performance under different operating conditions - in a city and the "start-stop" mode;
- Good foaming and corrosion resistance, compatible with seal materials;
- Increased engine cleanliness due to the high content of synthetic components;
- Stable viscosity characteristics during the entire operation period due to the exceptional stability of all components;

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	14,9
Density at 20°C, kg/m ³	886
Viscosity index	136
TBN mg KOH/g	5.8
Flash point in open crucible, °C	218
Pour point, °C	-30

Packing	Vendor code	Barcode
Canister plastic 1l	018079	482007024613
Bucket tin 20l	011906	482007024440
Canister plastic 4l	011887	482007024533
Canister plastic 5l	011809	482007024451