

SUPER GAS 15W-40

SEMI-SYNTHETIC ENGINE OIL FOR CARS EQUIPPED WITH LPG

SPECIFICATIONS:

SAE 15W-40

API SM

API CF

DESCRIPTION:

Semisynthetic motor oil specially produced for bi-fuel engines, equipped with LPG equipment (gas-petrol / gas-diesel) cars and vans that works in difficult operating conditions, urban traffic, "start-stop" mode. Effectively protects the engine against the high temperatures that occurs during the combustion of gaseous fuels.

Produced from high quality base oils using a unique synthetic components that provides viscosity grade SAE 15W-40.

APPROVAL:

MB 229.1

VW 501.00

BENEFITS:

- High performance under different operating conditions - in a city and the "start-stop" mode;
- Good foaming and corrosion resistance, compatible with seal materials;
- Increased engine cleanliness due to the high content of synthetic components;
- Stable viscosity characteristics during the entire operation period due to the exceptional stability of all components;

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	15.08
Density at 20°C, kg/m ³	855.90
Viscosity index	148
Alkalinity, mg KOH/g	5.78
Flash point in open crucible, °C	220
Pour point, °C	-35

Packing	Vendor code	Barcode
Barrel metal 200l	014605	
Canister plastic 20l	011909	