

# SUPER SYNTHETIC C2 0W-30

## SYNTHETIC MOTOR OIL.

### SPECIFICATIONS:

SAE 0W-30

API SN

API CF

ACEA C2

ILSAC GF-6A

### DESCRIPTION:

Fully synthetic low-viscosity engine oil for passenger car gasoline and diesel engines with and without turbo-charging and direct injection. Provides a safe layer of lubrication at high operating temperatures and protects from corrosion and loss of oil through oxidation or coking. The excellent cold start behavior ensures optimum lubrication safety during the cold running. It is optimally coordinated for prolonged drain intervals. Especially suitable for use in automobile gasoline and diesel engines with subsequent exhaust treatment systems (DPF), which require engine oils with ACEA C2 specification, according to the OEM manual.

### CONFORMITY:

FIAT 9.55535 DS1

FIAT 9.55535-GS1

PSA B71 2290

PSA B71 2312

Ford WSS-M2C950-A

MB 229.61

BMW LL-12 FE

CHRYSLER MS-13340

IVECO 18-1811

CLASSE SCI LV

JAGUAR LAND ROVER

STJLR.03.5007

### BENEFITS:

- Ensures a stable lubricating film over a wide temperature range;
- Reduction of fuel consumption and car exhaust emissions
- Excellent mechanical High Temperature High Shear (HTHS) rate stability throughout the entire service life.

### TYPICAL CHARACTERISTICS:

Viscosity mm <sup>2</sup> /s at 100 °C	9,3 - 12,5
Density at 20°C, kg/m <sup>3</sup>	900
Viscosity Index	140
Pour point °C	-38
Flash point in open crucible, °C	200

Packing	Vendor code	Barcode
Canister plastic 5l	021348	
Canister plastic 1l	019434	