

SUPER SYNTHETIC C4 5W-30

SYNTHETIC MOTOR OIL.

SPECIFICATIONS:

SAE 5W-30

API SN

API CF

ACEA C3

DESCRIPTION:

Longlife fuel-economy fully synthetic engine oil for all types of cars with petrol and diesel engines (including fuel injected engines, multivalve engines with or without turbo-charge, with or without catalytic converters of exhaust gas, with or without DPF).

Produced of high-quality synthetic base oils with additives, providing high performance of engine within a wide temperature range and extending its service life. Meets the requirements of Longlife service interval (WIV) of VAG group.

CONFORMITY:

MB 229.31

MB 229.51

VW 504.00/507.00

BMW LL-04

Porsche C30

Fiat 9.55535-G1

BENEFITS:

- Extreme wear protection & excellent viscosity-temperature behaviour
- Minimal frictional loss & Very high cleaning capability
- Low volatilization loss & High oxidation and temperature stability
- Reduces fuel consumption according API EC and reduces exhaust emission
- Excellent cold starting properties – rapid supply of all points of lubrication
- Very good operating reliability & multigrade usage
- Optimal engine cleanliness & lowest oil consumption
- High margin of performance & product stability
- Extended oil change intervals & prevents black sludge formation

TYPICAL CHARACTERISTICS:

Density at at 20°C kg/m ³	900
Flash point °C	200
Pour point °C	-35
Viscosity at 100°C mm ² /s 9,3 - 12,5	
Viscosity Index	140
TBN mg KOH/g	5,0

Packing	Vendor code	Barcode
Canister plastic 1l	019443	
Canister plastic 5l	017543	

0 800 60 5555

Telephone hotline