

VEGA SYNT 5W-40

HC-SYNTHETIC MOTOR OIL.

SPECIFICATIONS:

SAE 5W-40

API SL

API CF

ACEA A3/B4

DESCRIPTION:

Multigrade universal synthetic motor oil designed for petrol and diesel engines. Effectively protects and ensures engine running over a wide temperature range and in temperate climates. Recommended for engines with a standard drain intervals of both modern, and last generations.

CONFORMITY:

MB 229.3

VW 502.00

VW 505.00

BMW LL-01

BENEFITS:

- Retains its operational properties for as long as possible, which allows to increase engine oil change intervals;
- Absence of high-temperature and low-temperature deposits in the engine;
- Significantly lengthens the engine life due to the content of a multifunctional complex of additives;
- Reduces fuel consumption and exhaust emissions;
- Possesses excellent low-temperature, anti-friction, anti-corrosion, detergent and antioxidant properties;
- Low volatility at high operating temperatures.

TYPICAL CHARACTERISTICS:

Viscosity mm ² /s at 100 °C	13.2
Density at 20°C, kg/m ³	855
Viscosity Index	148
Pour point °C	-36
Flash point in open crucible, °C	224
TBN mg KOH/g	9.2

Packing	Vendor code	Barcode
Canister plastic 4l	020509	

JV YUKOIL LLC, 69014, Ukraine, Zaporizhia, Bazova str., 3a according to TU U 19.2-31852954-116: 2021.

The values in the table are typical for this product, have a reference character and are not may be a legal guarantee of the properties of the product or the suitability of the product for a particular application. The actual parameters of the product are reflected in the quality passport for each batch produced. The manufacturer reserves the right to change the product information at any time without notice. Technical support service: support@yuko.ua

0 800 60 5555

Telephone hotline