

YUKO ATF DSG

HIGH-PERFORMANCE PREMIUM-GRADE SYNTHETIC FLUID

DESCRIPTION:

High-performance premium-grade synthetic fluid for dual-clutch transmissions. The product is designed for robotic systems with friction discs immersed in oil, which ensure uninterrupted DSG / DCT operation in difficult operating conditions.

CONFORMITY:

VW G 052 178/182	VW TL 052 182	VW G 052 512/513/529	VW G 052 726/798/171	VW G 055 532
BMW DCTF-1/ MTF-LT-5	PSA 9734.S2	Renault Bot 450	Volvo Bot 341, 161838	Ford WSS M2C-936-A
Ford WSS-M2C-200-D2	MB 236.25- MB 236.21	Mitsubishi	Diamond Queen SSTF-1	

BENEFITS:

- Has a high thermal, oxidation stability and excellent pumpability (low temperature fluidity), providing uninterrupted operation of the machinery at extremely low temperatures;
- Excellent frictional properties;
- Ensures quiet operation;
- Extends transmission service life.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s#ASTM D445 or GOST 33	7,0 – 9,0
Density at 20°C, kg/m ³ #ASTM D1298 or GOST 3900	890
Viscosity index#ASTM D2270 or DSTU GOST 25371	160
Flash point in open crucible, °C#ASTM D92 or GOST 4333	185
Pour point, °C#ASTM D97 of GOST 20287	- 45

Packing	Vendor code	Barcode
Canister plastic 1l	019458	