

ATF III

MULTIPURPOSE ALL-SEASON POWER FLUID FOR AUTOMATIC GEARBOXES

DESCRIPTION:

Intended for automatic gearboxes, transmissions, servo drives (power steering) of passenger cars and trucks, buses, special vehicles, other hydraulic systems, where Dexron® III or Dexron® II fluids are recommended.

Produced on basis of foreign components. Coloured red.

APPROVAL:

GM DEXRON - III	Ford MERCON V	Allison C-4	MAN 339 type Z-2	Volvo 97340	ZF TE-ML 04D
ZF TE-ML 14B	ZF TE-ML 16L	ZF TE-ML 17C			

BENEFITS:

- Has a high thermal, oxidation stability and excellent pumpability (low temperature fluidity), providing uninterrupted operation of the machinery at extremely low temperatures;
- Provides easiness and smoothness of gear change in various operating modes;
- Ensures quiet operation;
- Excellent frictional properties;
- Extends transmission service life.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm²/s	7.5
Density at 20°C, kg/m³	865
Viscosity index	170
Flash point in open crucible, °C	200
Pour point, °C	-45

Packing	Vendor code	Barcode
Canister can 1l	021725	4820070241914