

YUKO ATF VI

UNIVERSAL ALL-SEASON WORKING FLUID FOR AUTOMATIC TRANSMISSIONS.

DESCRIPTION:

Newest fluid for automatic transmissions based on HC base oils and high-performance additives. The unique composition of the oil provides extended service intervals, excellent resistance to wear and oxidation, efficient operation at the lowest temperatures. Recommended for use in modern stepped automatic boxes and hydraulic mechanisms for controlling cars, minibuses and trucks.

APPROVAL:

GM DEXRON VI DEXRON III F/G/H DEXRON IID

CONFORMITY:

Aisin Warner JWS 3309 JWS 3324 AW-1 Audi VW G 052 162 G 055 162-A2 -A6
 BMW ZF 5HP18FL 5HP24 5HP30 Chrysler ATF+ +2 +3 Ford WSS M2C 922 A1
 924 A (XT-8-QAW) Honda ATF 3.1 DW-1 Hyundai KIA SP-IV-M Jaguar LT 71141 ZF 5HP 24
 Mazda ATF D-II M-III M-V FZ Toyota ATF T-III T-IV W Opel/GM 2217466 889200925
 9986195 Voith 55.6336.XX (G607) Volvo PN 116 1640 - 1621 VW G US 000 16 ZF TE-ML 09
 11A 11B 21 ZF 3 4 8 9 speed Transmissions

BENEFITS:

- Excellent frictional properties;
- Ensures quiet operation;
- Extends transmission service life.

TYPICAL CHARACTERISTICS:

Viscosity mm ² /s at 100 °C	7,5
Density at 20°C, kg/m ³	845
Viscosity Index	170
Pour point °C	-52
Flash point in open crucible, °C	205

Packing	Vendor code	Barcode
Tin can 1l	022043	4823110402283