

DYNAMIC 10W-40

UNIVERSAL MOTOR OIL WITH HIGH CONTENT OF SYNTHETIC COMPONENTS.

SPECIFICATIONS:

SAE 10W-40

API SG

API CD

DESCRIPTION:

Intended for gasoline and diesel engines of passenger cars, vans and light trucks according to manufacturers' instructions.

Produced of high-quality base oils with improved additives package containing synthetic components, providing high performance.

BENEFITS:

- Good anti-wear, antioxidant and dispersing properties;
- Increased engine cleanliness due to the high content of synthetic components;
- Easy cold start in winter;
- A wide range of packaging meets the requirements of any equipment.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	14,3
Density at 20°C, kg/m ³	885
Viscosity index	138
Alkalinity, mg KOH/g	5.1
Flash point in open crucible, °C	210
Pour point, °C	-32

Packing	Vendor code	Barcode
Barrel metal 200l	006081	482007024026
Canister plastic 5l	006080	482007024208
Canister plastic 4l	006125	482007024207
Canister plastic 1l	006079	482007024206

Produced according to TU U 23.2-31852954-045:2010. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.

0 800 60 5555

Telephone hotline