

# YUKO I-40A

## INDUSTRIAL SPECIAL OIL.

### SPECIFICATIONS:

ISO 68

### DESCRIPTION:

It is used as working fluids in hydraulic systems of machine tools, automatic lines, presses, for lubrication of light and medium-loaded gears, rolling and sliding guides of machine tools, where special oils are not required.

General-purpose oil, distillate or a mixture of distillate with residual from sulfurous and low-sulfur oils of selective purification. Contains no additives. I-40A oil is used in hydraulic systems of industrial equipment, for construction, road and other machines working outdoors.

\* According to TS, in the period from April to September, the freezing temperature can vary no higher than minus 10°C.

### BENEFITS:

- It ensures reduction of friction and wear of contacting parts;
- Removes heat from friction nodes;
- Protects parts from corrosion;
- Cleans friction surfaces from dirt;
- It is a sealing agent.

### TYPICAL CHARACTERISTICS:

Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	69,9
Density at 20 °C, kg/m <sup>3</sup>	885
Acid index, mg KOH/g max	0,05
Flash Point COC °C	226
Pour point, °C	-15

Packing	Vendor code	Barcode
Barrel metal 200l	000317	482007024114
Canister plastic 20l	005272	482007024076