

YUKO LITOL-24

A UNIVERSAL MULTIPURPOSE ANTIFRICTION WATERPROOF GREASE.

SPECIFICATIONS:

NLGI 3

DESCRIPTION:

Used for lubrication of friction units in wheeled and tracked vehicles, industrial equipment and ship machinery such as rolling and friction bearings of all types, hinges, gear and other transmissions, friction surfaces of industrial machinery, electric machines etc. Temperature range -40 °C ... + 120 °C (for a short moment up to 130 °C).

Produced from thickened petroleum oils blend with 12-hydroxy-stearic acid lithium soap with additional viscosity and antifriction additives.

BENEFITS:

- A universal multipurpose grease for lubrication of friction units of all types;
- Has good conservation properties;
- Extends the period of regular lubrication;
- Allowed to be used in closed nodes (car wheel hubs, water pumpsbearings etc.) as a substituted for general-purpose lubricants;
- High colloidal, chemical and mechanical stability;
- Variety of packing types, package volumes;

TYPICAL CHARACTERISTICS:

Dropping point, °C	196
Penetration, mm • 10 -1	235
Colloid stability, %	6,5
Evaporation at 120 °C, %	1,5

Packing	Vendor code	Barcode
Barrel 200l	005132	482007024137
Bucket tin 17kg	001280	482007024139
Cartouche plastic 0.4l	015935	482007024647
Bucket plastic 9kg	004906	482007024138
Bucket plastic 4.5kg	005428	482007024197
Tin can 1l	008624	482007024247
Doi-pack plastic 0.375l	004352	482007024136
Doi-pack plastic 0.15l	012291	482007024393