

MASTER SYNT 4T 10W-30

SEMISYNTHETIC MOTOR OIL FOR FOUR-STROKE ENGINES.

SPECIFICATIONS:

SAE 10W-30

API SL

API CF

JASO MA2

JASO T903:2016

DESCRIPTION:

Used for lubricating systems of modern four-stroke engines of garden machinery and power equipment: mowers, cultivators, generators, motor pumps, snow-removing machines and other four-stroke machinery.

A modern additives package, provides performance stability throughout the service life, ensuring a high level of reliability and low-temperatures stability. Minimizes exhaust smoking and emissions toxicity.

BENEFITS:

- Year-round use;
- Designed for the engines of frequently used garden machinery and power equipment;
- Due to the special high-viscosity formula, forms a durable oil film, capable of withstanding the continuous loads;
- Minimum evaporation loss rate, therefore - low consumption;
- Provides effective protection of the engine parts against corrosion and carbon formation;
- Improves engine compression, increasing its power.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	10,8
Viscosity index	140
Alkalinity, mg KOH/g	6,7
Pour point, °C	-32

Packing	Vendor code	Barcode
Oilbox carton polyethylene 20l	022523	4823110402726
Canister plastic 1l	010215	4820070240450
Tin can 600ml	023243	4823110403273