

MEGA DIESEL 15W-40

ALL-SEASON MOTOR OIL FOR MODERN DIESEL ENGINES.

SPECIFICATIONS:

SAE 15W-40

API CI-4

API SL

ACEA E7

DESCRIPTION:

Intended for year-round use in high-speed air and turbo diesel engines of long-distance trucks, agricultural and construction machinery, buses and other commercial vehicles.

Produced of selected base oils with effective additives package, providing optimum antifriction, anticorrosion, detergent and antioxidizing properties.

Licensed by API. Tolerances MB, Cummins, Volvo, Renault, Caterpillar.

APPROVAL:

Volvo VDS-3

Mack EO-N

Renault VI RLD-2

MB 228.3

MAN M3275-1

Cummins CES 20076/77

MTU Type 2

Caterpillar ECF-1a

Deutz DQC III-10

CONFORMITY:

MB 228.3

MAN M3275-1

Cummins CES 20076/77

MTU Type 2

Caterpillar ECF-1a

Deutz DQC III-10

Volvo VDS-3

Renault RLD-2

CES 20076/77

ECF-1a

DQC III-10

BENEFITS:

- Consistently high performance in various operating modes over a long period of time;
- Improved anti-foam properties, which significantly reduces the risk of foam formation in the hydraulic circuit of valves;
- Compatible with all engine sealings;

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	14.9
Density at 20°C, kg/m ³	880
Viscosity index	140
Alkalinity, mg KOH/g	9.2
Flash point in open crucible, °C	225
Pour point, °C	-30

Packing	Vendor code	Barcode
Barrel metal 200l	005079	482007024055
Bucket tin 20l	005276	482007024054