

## SCOOTER SYNT 2T (FC)

### SEMISYNTHETIC MOTOR OIL FOR TWO-STROKE ROAD MACHINERY.

#### SPECIFICATIONS:

API TC

JASO FC

#### DESCRIPTION:

Intended for two-stroke engines of air-cooled road machinery such as: modern motorcycles, motorbikes, scooters, snowmobiles and other two-stroke machinery.

Used as a component in oil-fuel blend in a ratio recommended by machines manufacturer. Standard injection varies from 1:32 to 1:50.

Produced of high-quality base oils with selected active additives package.

#### BENEFITS:

- Provides best lubricating, anti-wear, anticorrosion and detergent properties incl. extreme loads;
- Has optimal quality level for two-stroke engines of modern machinery;
- Ideal for vehicles manufactured in Japan, China and South-East Asia, as it corresponds to specifications of JASO FC (Japan);
- Minimizes exhaust smoking, which allows to use this oil in conditions of strict environmental regulations;
- The possibility of application in separate lubricating systems for two-stroke engines;
- Contains active additives package of new generation, providing increased engine cleanliness;
- Good fuel-miscible even at low temperatures.

#### TYPICAL CHARACTERISTICS:

|  |     |
|--|-----|
| Kinematic viscosity at 100°C, mm <sup>2</sup> /s | 7,7 |
| Density at 20°C, kg/m <sup>3</sup>               | 875 |
| Viscosity index                                  | 98  |
| Alkalinity, mg KOH/g                             | 0,8 |
| Flash point in open crucible, °C                 | 110 |
| Pour point, °C                                   | -15 |

| Packing         | Vendor code | Barcode |
|-----------------|-------------|---------|
| Canister can 1l | 021591      |         |