

SCOOTER SYNT 2T (FC)

SEMISYNTHETIC MOTOR OIL FOR TWO-STROKE ROAD MACHINERY.

SPECIFICATIONS:

API TC

JASO FC

DESCRIPTION:

Intended for two-stroke engines of air-cooled road machinery such as: modern motorcycles, motorbikes, scooters, snowmobiles and other two-stroke machinery.

Used as a component in oil-fuel blend in a ratio recommended by machines manufacturer. Standard injection varies from 1:32 to 1:50.

Produced of high-quality base oils with selected active additives package.

BENEFITS:

- Provides best lubricating, anti-wear, anticorrosion and detergent properties incl. extreme loads;
- Has optimal quality level for two-stroke engines of modern machinery;
- Ideal for vehicles manufactured in Japan, China and South-East Asia, as it corresponds to specifications of JASO FC (Japan);
- Minimizes exhaust smoking, which allows to use this oil in conditions of strict environmental regulations;
- The possibility of application in separate lubricating systems for two-stroke engines;
- Contains active additives package of new generation, providing increased engine cleanliness;
- Good fuel-miscible even at low temperatures.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	7,7
Density at 20°C, kg/m ³	875
Viscosity index	98
Alkalinity, mg KOH/g	0,8
Flash point in open crucible, °C	110
Pour point, °C	-15

Packing	Vendor code	Barcode
Tin can 1l	021591	