

## SCOOTER SYNT 2T (FC)

### SEMISYNTHETIC MOTOR OIL FOR TWO-STROKE ROAD MACHINERY.

#### SPECIFICATIONS:

API TC

JASO FC

#### DESCRIPTION:

Intended for two-stroke engines of air-cooled road machinery such as: modern motorcycles, motorbikes, scooters, snowmobiles and other two-stroke machinery.

Used as a component in oil-fuel blend in a ratio recommended by machines manufacturer. Standard injection varies from 1:32 to 1:50.

Produced of high-quality base oils with selected active additives package.

#### BENEFITS:

- Provides best lubricating, anti-wear, anticorrosion and detergent properties incl. extreme loads;
- Has optimal quality level for two-stroke engines of modern machinery;
- Ideal for vehicles manufactured in Japan, China and South-East Asia, as it corresponds to specifications of JASO FC (Japan);
- Minimizes exhaust smoking, which allows to use this oil in conditions of strict environmental regulations;
- The possibility of application in separate lubricating systems for two-stroke engines;
- Contains active additives package of new generation, providing increased engine cleanliness;
- Good fuel-miscible even at low temperatures.

#### TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	7,7
Density at 20°C, kg/m <sup>3</sup>	875
Viscosity index	98
Alkalinity, mg KOH/g	0,8
Flash point in open crucible, °C	110
Pour point, °C	-15

Packing	Vendor code	Barcode
Canister	004904	482007024160
plastic 1l		

Produced according to TU U 23.2-31852954-035:2008. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.

**0 800 60 5555**

Telephone hotline