

# SEMISYNTHETIC 10W-40

## SEMISYNTHETIC PREMIUM MOTOR OIL.

### SPECIFICATIONS:

SAE 10W-40

API SN

API CF

ACEA A3/B4

### DESCRIPTION:

Intended for modern gasoline and diesel engines of passenger cars and vans (injector, multivalve, turbocharged, including fitted with exhaust fumes catalyts). It is an optimum choice for vast majority of foreign passenger cars and vans.

Produced of high-quality base oils with well-balanced additives package, providing good antifricition, anticorrosion, detergent and antioxidizing properties.

### CONFORMITY:

VW 502.00/505.00

MB 229.1, 229.3

PSA B71 2300

BMW Special

Renault RN 0700, RN 0710

Fiat 9.55535 D2/G2

MB 229.1/229.3

VW 502.00/VW 505.00

Renault RN 0700

RN 0710

MB 229.1

229.3

### BENEFITS:

- Consistently high performance in various operating modes;
- Easy cold start in winter;
- Prevents high and low temperature deposits formation in the engine;
- High-class performance properties allows using YUKO Semisynthetic 10W-40 in the engines of the most modern cars;
- Compatible with all engine sealings;
- A wide range of packaging meets the requirements of any equipment.

### TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	14.5
Density at 20°C, kg/m <sup>3</sup>	880
Viscosity index	151
Alkalinity, mg KOH/g	9.3
Flash point in open crucible, °C	210
Pour point, °C	-30

Packing	Vendor code	Barcode
Canister can 5l	020662	
Oilbox carton polyethylene 20l	019797	
Barrel metal 200l	000169	482007024014
Bucket tin 20l	009785	482007024023
Canister plastic 5l	000096	482007024168
Canister plastic 4l	000095	482007024015
Canister plastic 1l	000094	482007024016