

SEMISYNTHETIC 4T 10W-40

SEMISYNTHETIC ALL-SEASON MOTOR OIL FOR FOUR-STROKE ENGINES.

SPECIFICATIONS:

SAE 10W-40

API SL

JASO MA2

JASO T903:2016

DESCRIPTION:

Intended for lubricating systems of modern four-stroke engines of motorcycles, ATVs, scooters and other motor vehicles with any clutch type, and for the power equipment.

Using in water-cooled outboard engines is acceptable.

Produced of high-quality foreign mineral base oils with premium additives package.

BENEFITS:

- Has high thermal stability and excellent detergency;
- Provides high anti-wear protection within a wide load range;
- Provides effective overheat protection for the engine;
- Minimizes exhaust smoking and emissions toxicity;
- Contains modern premium additives package;
- Excellent stability of viscosity rating within the viscosity grade throughout the service life;

TYPICAL CHARACTERISTICS:

| | |
|--|------|
| Kinematic viscosity at 100°C, mm ² /s | 14,0 |
| Density at 20°C, kg/m ³ | 873 |
| Viscosity index | 143 |
| Alkalinity, mg KOH/g | 6,1 |
| Flash point in open crucible, °C | 215 |
| Pour point, °C | -32 |

| Packing | Vendor code | Barcode |
|------------------------|-------------|--------------|
| Canister plastic 1l | 004878 | 482007024193 |