

YUKO SOLIDOL EXTRA

GENERAL PURPOSE CALCIUM GREASE

SPECIFICATIONS:

NLGI 2/3

DESCRIPTION:

Solidol is used for lubrication of rough friction nodes in machines and mechanisms of vehicles, agricultural machinery, hand and other tools, screw and chain gears, low-speed gear reducers, etc. at temperature -25°C to +65°C.

Solidol grease is produced from pure base oil of medium viscosity, thickened with hydrated ring soap of fatty acids of vegetable and animal fats.

BENEFITS:

- You can buy Solidol in any volume, since during long-term storage it almost does not compact;
- Differs in favorable viscosity-temperature properties;
- Excellent extreme pressure properties and resistance to wear;
- High colloidal stability;
- Excellent chemical and mechanical properties;
- Solidol has a large selection of types of packaging, packaging volumes;
- Compliance with GOST.

TYPICAL CHARACTERISTICS:

Dropping point, °C	95
Penetration at 25°C, mm×10 ⁻¹	260
Tensile strength at 50°C, Pa	450

Packing	Vendor code	Barcode
Barrel 200l	005130	482007024149
Bucket tin 17kg	003728	482007024143
Cartouche plastic 0.4l	016303	482007024648
Bucket plastic 9kg	004905	482007024142
Bucket plastic 4.5kg	005429	482007024192
Tin can 1l	008627	482007024251
Doi-pack plastic 0.375l	004353	482007024140
Doi-pack plastic 0.15l	012292	482007024386