

SUPER SYNT 2T (FC)

SEMI-SYNTHETIC MOTOR OIL FOR TWO-STROKE ENGINES.

SPECIFICATIONS:

API TC

JASO FC

DESCRIPTION:

Intended for using in two-stroke engines, garden and other air and water-cooled machinery.

Application in the road machinery is acceptable as well, especially where exhaust smoking restriction requirements exist.

YUKO Super Synt 2T Green Garden conforms to the requirements of API TC, and JASO FC.

Used as a component in oil-fuel blend in a ratio recommended by machines manufacturer. Standard injection varies from 1:32 to 1:50.

BENEFITS:

- Provides good lubricating, anti-wear, anticorrosion and detergent properties;
- Environment-friendly as it is smoke-free and biodegradable;
- Low-ash oil formula prevents carbon and lacquer formation;
- Provides improved engine cleanliness due to the content of synthetic components;
- The possibility of year-round use;
- Contains active additives package;
- Compatible with all engine sealings.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	8.1
Density at 20°C, kg/m ³	879
Viscosity index	135
Alkalinity, mg KOH/g	0.9
Flash point in open crucible, °C	90
Pour point, °C	-15

Packing	Vendor code	Barcode
Canister plastic 1l	004886	482007024159