

SUPER SYNTHETIC C3 5W-40

HC-SYNTHETIC ENGINE OIL.

SPECIFICATIONS:

SAE 5W-40

API SN

API CF

ACEA C3

DESCRIPTION:

Synthetic base oil components and adapted innovative additives technology ensure smooth and reliable engine performance. The improved quality of YUKO SUPER SYNTHETIC SAE 5W-40 particularly results in further improved anti-wear protection and engine cleanliness, even during extended oil drain intervals. The extreme low viscosity at low temperature combined with a reliable high temperature viscosity and low volatility assures a high fuel economy capacity. It contributes through its high fuel economy and reduction of emissions to protect the environment. YUKO Super Synthetic SAE 5W-40 has been developed primarily for application in diesel powered engines with exhaust reduction system to meet the emission standards of Euro IV. It is suitable as high performance low friction engine oil for use in a new sophisticated generation of engines and recommended for gasoline and diesel engines of all passenger cars operating in various conditions, including the turbocharged and direct injected versions equipped with catalyst.

CONFORMITY:

VW 502.00/505.00/505.01

MB 229.31, 229.51

BMW LL-04

Renault RN17

MB 229.31

MB 229.51

MB 229.52

Porsche C30

GM Dexos 2

Ford WSS-M2C 917A

BENEFITS:

- Extreme wear protection and excellent viscosity-temperature behaviour
- Minimal frictional loss & Very high cleaning capability
- Low volatilization loss & High oxidation and temperature stability
- Reduces fuel consumption according API EC and reduces exhaust emission
- Excellent cold starting properties – rapid supply of all points of lubrication
- Very good operating reliability & multigrade usage
- Optimal engine cleanliness & lowest oil consumption
- High margin of performance & product stability
- Extended oil change intervals & prevents black sludge formation

TYPICAL CHARACTERISTICS:

| | |
|---------------------------------------|-------|
| Density at 20°C kg/m ³ | 850 |
| Flash point °C | 227 |
| Pour point °C | -45 |
| Viscosity at 100°C mm ² /s | 14.75 |
| Viscosity Index | 165 |
| TBN mg KOH/g | 6,9 |

| Packing | Vendor code | Barcode |
|-------------------|-------------|---------------|
| Barrel metal 200l | 017838 | 4820070241501 |
| Tin can 1l | 022867 | 4823110402276 |
| Tin can 4l | 021595 | 4823110401538 |