

# SYNTHETIC 5W-40

## SYNTHETIC HIGH-TECH MOTOR OIL.

### SPECIFICATIONS:

SAE 5W-40

API SN

API CF

ACEA A3/B4

### DESCRIPTION:

Intended for modern gasoline and diesel engines of passenger cars and vans. Compatible with injector and multivalve engines, including turbocharged, with intercooler and catalyst.

Produced of high-quality foreign synthetic base oils with additives, providing high performance of engine within a wide temperature range and extending its service life.

Provides increased safety level as compared to mineral and semi-synthetic oils. Special low-ash formula. Has an extended drain interval.

### CONFORMITY:

VW 502.00/505.00

MB 229.3, MB 229.5

PSA B71 2296

BMW LL-01

Renault RN0700, RN0710

Opel GM-LL-B025

Porsche A40

MB 229.5

MB 226.5

Renault RN0700

RN0710

## BENEFITS:

- Provides a reliable engine protection under various conditions incl. extreme operating mode;
- Optimum for the use both in urban cycle and cross-country conditions;
- Due to its fluidity reduces fuel consumption;
- Significantly extends engine service life due to multipurpose additives package content, with excellent low temperature, antifriction, anticorrosion, detergent and antioxidizing properties;
- Maintains effectiveness for maximum long period, which allows to extend significantly oil drain intervals;
- Due to superior viscosity/temperature properties provides safe engine start at low temperatures in winter, including the regions with harsh weather conditions in winter;
- Conforms to modern requirements of world leaders in equipment manufacture concerning oil consumption, volatility, energy saving.

## TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	14.7
Density at 20°C, kg/m <sup>3</sup>	855
Viscosity index	167
TBN mg KOH/g	10.2
Flash point in open crucible, °C	211
Pour point, °C	-42

Packing	Vendor code	Barcode
Canister plastic 20l	021318	4820070248395
Tin can 4l	021597	4820070241167
Tin can 1l	021583	4820070241150