

TURBO DIESEL 15W-40

ALL-SEASON MINERAL MOTOR OIL FOR DIESEL ENGINES.

SPECIFICATIONS:

SAE 15W-40

API CD

API SF

ACEA E2

ACEA E5

DESCRIPTION:

Intended for year-round use in air and turbo diesel engines of passenger cars, vans, trucks incl. turbocharged.

Produced of mineral base oils with modern additives, providing the properties significantly surpassing similar class oils.

The most suitable oil for the transfer of the diesel engines from one season oils (classes M10G2k, M10DM) to all-season ones.

Using in gasoline engines is acceptable in accordance with car manufacturers' instructions.

BENEFITS:

- Good lubricating, detergent and anticorrosion properties;
- Good protection against high and low temperature deposits formation in the engine;
- Optimum for most common models of diesel engines;
- Compatible with all engine sealings;
- Ideal price/quality ratio;
- The most suitable oil for the transfer of the diesel engines from one season oils to all-season ones.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	14.8
Density at 20°C, kg/m ³	895
Viscosity index	115
Alkalinity, mg KOH/g	7.2
Flash point in open crucible, °C	225
Pour point, °C	-25

Packing	Vendor code	Barcode
Barrel metal 200l	000178	482007024061
Bucket tin 20l	004566	482007024059
Oilbox carton polyethylene 20l	018313	482007024338
Canister plastic 5l	005738	482007024060