

# TURBOSYNT DIESEL 10W-40

SEMI-SYNTHETIC MOTOR OIL FOR DIESEL ENGINES.

## SPECIFICATIONS:

SAE 10W-40

API CH-4

API SL

ACEA E2

ACEA E5

## DESCRIPTION:

Intended for modern air and turbo diesel engines of passenger cars, vans and trucks and other commercial vehicles.

Produced of high-quality foreign base oils with additives, providing optimum performance throughout the service life.

## CONFORMITY:

MB 228.1

MAN M271

Volvo VDS/VDS-2

## BENEFITS:

- Consistently high performance in various operating modes;
- Optimum lubricating properties and detergency;
- Easy cold start in winter;
- Prevents high and low temperature deposits formation in the engine;
- Reliable wear protection of engine parts throughout the service life;
- Compatible with all engine sealings;

## TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	14.9
Density at 20°C, kg/m <sup>3</sup>	885
Viscosity index	134
Alkalinity, mg KOH/g	8,5
Flash point in open crucible, °C	223
Pour point, °C	-32

Packing	Vendor code	Barcode
Barrel metal 200l	006085	482007024057
Bucket tin 20l	007890	482007024056
Canister plastic 5l	006084	482007024205
Canister plastic 1l	006083	482007024204