

VEGA SYNT 10W-40

SEMISYNTHETIC HIGH-QUALITY HYDROCRACKING MOTOR OIL.

SPECIFICATIONS:

SAE 10W-40

API SL

API CF

ACEA A3/B4

DESCRIPTION:

Intended for gasoline and diesel engines of passenger cars and vans (injector, multivalve, turbocharged, including fitted with exhaust fumes catalysts).

Produced according to hydrocracking technology of high-quality base oils with active additives package providing stable performance. Effectively prevents carbon and lacquer formation.

CONFORMITY:

VW 502.00/505.00

MB 229.1

PSA E/D-02 Level 2

VW 505.00

VW 505.01

BENEFITS:

- Reliable engine lubrication at any temperatures;
- Easy cold start at sub-zero temperatures;
- Due to the high content of synthetic components, the oil provides improved engine cleanliness;
- No high and low temperature deposits in the engine;
- Low volatility at high operating temperatures;
- A wide range of packaging meets the requirements of any equipment;

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	13.7
Density at 20°C, kg/m ³	877
Viscosity index	152
TBN mg KOH/g	9.6
Flash point in open crucible, °C	218
Pour point, °C	-39

Packing	Vendor code	Barcode
Barrel metal 200l	004786	482007024025
Bucket tin 20l	009786	482007024123
Canister plastic 5l	004871	482007024212
Canister plastic 4l	004487	482007024122
Canister plastic 1l	004489	482007024121