Motor Oil DIESEL SAE 30

Printed: 09.03.2021 version 1.0

Internal Product Code: 20533

page 1 of 09

SECTION 1: Chemical product identification and information about manufacturer

1.1 Product identification

Motor oil DIESEL SAE 30 Synonyms - absent.

1.2 Recommendations and restrictions on the use of chemical products Motor oil for gasoline and diesel internal combustion engines.

1.3 Information about supplier of Safety Data Sheet for the mixture

Company: LLC "JV YUKOIL" Bazova St, 3a Locality: Zaporozhye, Ukraine Phone number: +38 061 222 80 32 Telefax: +38 061 222 80 32 The contact person: FEA Department E-mail: support@yukoil.com Internet: https://yuko.ua Reference Department: FEA Department

1.4 Emergency telephone

Emergency phone number: +38 061 270 50 81

SECTION 2: Hazard Identification

2.1 Classification of substances and mixtures

This substance is not classified as hazardous according to Directive (EU) No 1272/2008 as amended.

2.2 Label elements (EC) No 1272/2008, 67/548/EEC aбo 1999/45/EC

The product is not subject to mandatory labelling with EU directives.

2.3 Other risk factors

Allergic reactions may occur. Product vapors may irritate the respiratory tract, skin and eyes. Harmful to health if swallowed. Do not allow product that has leaked to soak into the ground. Avoid uncontrolled release of product into the environment.

SECTION 3: Composition, information on ingredients

3.2 Mixtures (EU) No 1272/2008

Composition of hazardous substances

№ European Commission	CAS-number	Percentage (by weight)	Name	Classification
278-012-	74869-22-0	<95%	Mineral (base) oil	In clause 8.1
274-263-7	70024-69-0	1,4% to 2,8%	Benzenesulfonic acid, mono-C16-24-alkyl derivs., Calcium salts	Eye Irrit. 2; H319
283-392-8	84605-29-8	0,3% to 0,7%	Phosphorodithioic acid, mixed O, O-bis (1,3- dimethylbutyl and iso-Pr) esters, zinc salts)	Skin Irrit. 2; H315 Eye Damage 1; H31 8 Aquatic Chronic 2; H411

Safety Data Sheet

Prepared in accordance with Commission Regulation (EU) No 453/2010

Motor Oil DIESEL SAE 30

Printed: 09.03.2021 version 1.0

Internal Product Code: 20533

page 2 of 09

67/548/ЕЕС или 1999/45/ЕС

Unsafe composition of substances

№ European Commission	CAS-number	Percentage (by weight)	Name	Classification 67/548/EEC
278-012-2	74869-22-0	<95%	Mineral (base) oil	In clause 8.1
274-263-7	70024-69-0	1,4% to 2,8%	Benzenesulfonic acid, mono-C16-24-alkyl derivs., Calcium salts	Xi R36
283-392-8	84605-29-8	0,3% to 0,7%	i neepnereannere aera,	N Xi R38 R41 R51/53

Contains ingredients that are not subject to declaration according to current safety and regulatory criteria. For the explanatory text of R-phrases, see section 16.

Further instructions

DMSO - Extract <3%, IP 346.

PCB concentration <1 mg/kg.

Classification system: the classification is in accordance with the current EU lists, however, supplemented by data from special literature and company data.

SECTION 4: First aid measures

4.1 Description of first aid measures

When inhaling

In case of loss of consciousness, place the victim in a comfortable position and seek medical care. If symptoms persist, consult a doctor.

lf on skin

Wash affected area with plenty of water and neutral soap. Seek medical care if skin irritation occurs. Contaminated clothing should be washed before reuse.

In contact with eyes

In case of contact with eyes, rinse immediately with plenty of running water for at least 5 minutes. Then consult a doctor.

When ingested

Do not induce vomiting. Seek medical care immediately.

4.2 Most important symptoms and effects, both acute and delayed

See section 11

4.3 Indication of any immediate medical attention and special treatment needed

Information for the doctor: symptomatic treatment

SECTION 5: Measures and means of ensuring fire and explosion safety

5.1 Firefighting equipment

To extinguish fires use water spray, foam, powder, extinguishing agents or carbon dioxide (CO₂).

Firefighting equipment which must not be used for safety reasons

Powerful flow of water

5.2 Hazards associated with the substance or mixture

In case of fire, carbon monoxide, carbon dioxide (CO2), sulphur oxides, phosphorus oxides, nitrogen oxides may occur.

Motor Oil DIESEL SAE 30

Printed: 09.03.2021 vesion 1.0

Internal Product Code: 20533

page 3 of 9

5.3 Firefighting instructions

Special protective equipment for firefighting

In case of fire, self-contained breathing apparatus is recommended.

Additional instructions

Standard procedures for the elimination of chemical fires Use fire-fighting measures that comply with local laws and protocols for emergency localization and elimination.

SECTION 6: Measures for the prevention and elimination of emergency situations

6.1 Perosnal safety measures, protective equipment and emergency procedures

Use a set of personal protective equipment. Avoid contact with skin, eyes and clothing. Personal insecurity - slipping on a spilled product. Localize sources of ignition. When vapors, dust and aerosols are released, use respiratory equipment.

6.2 Environmental measures

Prevent entry into sewage and water bodies. If released into the atmosphere or if the product enters waterways, soil or sewers, notify the local authorities. Prevent surface spread (e.g. localize or protect against spilage).

6.3 Methods and materials for localization and purification

Collect loose liquid for recycling and / or disposal. Residues of the product can be collected with an inert material (sand, diatomaceous earth, universal sorbing agents, sawdust, cloth). Deal with contaminated material in accordance with section 13.

6.4 References to other sections

See sections 7, 8 and 13 for more information.

SECTION 7: Rules of conduct and storage

7.1 Protective measures to ensure safety when working with the substance

Guidelines for safe behavior

Provide ventilation at the workplace (there must be exhaust ventilation in the room). Avoid contact with skin, eyes and clothing, inhalation of product vapors.

Hygiene measures

Be sure to wash your hands before breaks and after work. Use a protective skin cream. If the product gets on your clothes, wash it off immediately and clean it thoroughly before reuse.

Instructions on fire and explosion protection

Take precautions against static electricity build-up (grounding during pumping / overflowing operations). Avoid the formation of oil mist.

Keep away from open sources of ignition, refrain from smoking when handling the product.

7.2 Conditions for safe storage, including any incompabilities

Requirements for warehouses and containers

Keep product packaging dry and sealed to prevent contamination, moisture and direct sunlight.

Storage conditions

Store separately from food, drink and animal feed. Do not store together with strong oxidants.

Further information about warehouse storage

Recommended storage temperature: 20 ± 10 ° C. Protect from heat, UV radiation, direct sunlight.

SECTION 8: Measures for the influence control and personnel protection

8.1 Control parameters

The product does not contain significant quantities of substances with concentration limit values that need to be monitored at the workplace. During the manufacture, they are guided by applicable laws and regulations.

Other substances with TLV

Contains mineral oil. Oil mist may form.

Motor Oil DIESEL SAE 30

Printed: 09.03.2021 vesion 1.0

Internal Product Code: 20533

page 4 of 9

Recommended value limits for oil mist: TWA: 5 mg/m 3 STEL: 10 mg/m 3

8.2 Control of harmful influences

Provide adequate ventilation and local exhaust ventilation in critical areas.

Personal protective measures

After handling products before eating, smoking, using the toilet and at the end of work wash hands and face. Take off dirty clothes. Contaminated clothing should be washed before reuse. Do not eat, drink or smoke in the workplace.

Eye protection

Tightly sealed safety goggles. DIN - ZEN - standards: EN 166

Respiratory protection

Not required If exhaust ventilation is not possible or insufficient, breathing apparatus should be worn.

Hand protection

Oil resistant protective gloves Tested protective gloves must be worn: DIN - ZEN - standards: EN 374. Suitable material: NBR (nitrile rubber). The time of loss of mechanical integrity and the swelling characteristics of the material must be taken into account. Preventive skin protection with a protective cream.

Body protection

Wear suitable protective clothing when working.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	liquid (under normal conditions)
Colour	from light yellow to dark brown
Scent	specific, not annoying
Flash point	more than 205 °C
Water solubility	insoluble
Kinematic viscosity at 100 ° C	11,5 sSt
Ignition temperature	more than 300 °C
Density at 20 ° C	not more than 0,910 g/cm ³
Pour point	minus 15 °C

The above data are typical and not a specification.

SECTION 10: Stability and chemical activity

10.1 Reactivity

Read carefully all the information provided in sections 10.2 - 10.6.

10.2 Stability

The material is generally stable at room temperature and pressure. See section 7 for details.

10.3 Possiblity of hazardous reactions

Absent

10.4 Conditions to avoid

See section 7, no further action is required. To avoid thermal decomposition - do not overheat.

10.5 Incompatible materials

Oxidants, compressed oxygen

10.6Hazardous decomposition materials

The product is stable under normal conditions of storage and use.

Thermal decomposition

Smoke, carbon monoxide (CO), carbon dioxide (CO2), aldehydes and other products of incomplete combustion. Sulfur oxides, phosphorus oxides, hydrogen sulfide, alkyl mercaptans and sulfides can be released.

Motor Oil DIESEL SAE 30

Printed: 09.03.2021 vesion 1.0

Internal Product Code: 20533

SECTION 11: Toxicological information 11.1 Information about toxicological effects

Acute toxicity

Oral

The half-lethal dose of LD_{50} for white rats is more than 5000 mg / kg. Results are based on data from components or similar products.

Dermal

Half-lethal dose LD₅₀ for rabbits is more than 2000 mg / kg. Results are based on data from components or similar products.

Inhalation

There is no evidence that the product or its components may present a toxicological hazard by inhalation.

Skin damage/irritation

May cause mild skin irritation. Results are based on data from components or similar products. Prolonged or repeated skin contact with clothing soaked in the material may cause dermatitis. Symptoms may include redness, rash, swelling, dryness, and cracking of the skin.

Serious eye injury / damage

No eye irritation expected. Results are based on data from components or similar products.

Respiratory tract irritation

If the material smokes or emits vapors when heated, their exposure may cause some irritation of the mucous membranes and upper respiratory tract. Results are based on data from components or similar products.

Respiratory tract and skin sensitization

Skin

There is no evidence that the product or its components cause skin sensitization.

Breathing

There is no data to indicate that the product or its components may be respiratory sensitizers.

Germ cell mutagenesis

There are no data on mutagenesis or genotoxicity of the product or its components present in concentrations above 0.1%.

Carcinogenecity

This product is believed to contain highly refined petroleum products and is not a carcinogen according to IARC. All oils contained in this product contain less than 3% extracted substances in accordance with the IP 346 test.

Reproductive toxicity

There is no data that the product or its components affect reproductive function at concentrations of more than 0.1%.

Repeated Exposure to Specific Organ Toxicity (STOT)

There are no data on the hazards of chronic exposure to the product or its components present in concentrations exceeding 1%.

Other information

No other health threats known.

Mineral (base) oil CAS # 74869-22-0

Acute toxicity

Oral

The half-lethal dose of LD_{50} for white rats is more than 5000 mg / kg. Results are based on data from components or similar products.

Dermal

Half-lethal dose LD₅₀ for rabbits is more than 2000 mg / kg. Results are based on data from components or similar products.

Inhalation

Information indicating that a product or its components may present a toxicological hazard by inhalation.

Irritation

Skin

May cause mild skin irritation. Results are based on data from components or similar products. Prolonged or repeated skin contact with clothing soaked in the material may cause dermatitis. Symptoms may include redness, rash, swelling, dryness, and cracking of the skin.

Eyes

Motor Oil DIESEL SAE 30

Printed: 09.03.2021 vesion 1.0

Internal Product Code: 20533

page 6 of 9

No eve irritation expected. Results are based on data from components or similar products.

Respiratory tract

If the material smokes or emits vapors when heated, their exposure may cause some irritation of the mucous membranes and upper respiratory tract. Results are based on data from components or similar products.

Sensitivity increase

Skin

There is no evidence that the product or its components cause skin sensitization.

Respiratory tract

There is no evidence that the product or its components may be a sensitizer for the respiratory tract.

Eyes

There is no evidence that the product or its components cause sensitization of the eyes.

Chronic toxicity

There are no data on the hazards of chronic exposure to the product or its components present in concentrations exceeding 1%.

Carcinogenecity

This product is believed to contain highly refined petroleum products and is not a carcinogen according to IARC. All oils in this product contain less than 3% extractables according to IP 346 test.

Mutagenicity

There is no data on the mutagenicity or genotoxicity of the product or its components.

Reproductive toxicity

There is no data indicating that the product or its components affect reproductive function.

Other information

No other health threats known

Benzenesulfonic acid, mono-C16-24-alkyl derivs., Calcium salts CAS # 70024-69-0

Acute toxicity

Oral

Half-lethal dose LD50 over 16000 mg / kg for rats

Dermal

Half-lethal dose LD50 for rats over 2000 mg / kg

Inhalation

The semi-lethal concentration of LC50 is more than 1.9 mg / I when exposed to the whole body for 4 hours

Irritation

Skin

Irritating to skin. The results are based on data for components or similar products. Prolonged or repeated skin contact with clothing soaked in the material may cause dermatitis. Symptoms may include redness, rash, swelling, dryness, and cracking of the skin.

Eves

Eye irritation possible. Results are based on data from components or similar products.

Airways

If the material smokes or emits vapors when heated, their influence may cause some irritation of the mucous membranes and upper respiratory tract. Results are based on data from components or similar products.

Sensitivity increase

Skin

There is no evidence that the product or its components cause skin sensitization.

Airways

There is no data to indicate that the product or its components may be respiratory sensitizers.

Eves

There is no evidence that the product or its components cause sensitization of the eyes.

Chronic toxicity

NOEL is defined as 1000 mg / kg / day for rats.

Motor Oil DIESEL SAE 30

Printed: 09.03.2021 vesion 1.0

Internal Product Code: 20533

page 7 of 9

Carcinogenecity

No data available

Mutagenicity

No data available

Reproductive toxicity

NOAEL 160 mg / kg / day. The results are based on data for components or similar products.

Other information

No other health threats known

Phosphorodithioic acid, mixed O, O-bis (1,3-dimethylbutyl and iso-Pr) esters, zinc salts CAS # 84605-29-8 Acute toxicity

Oral

Half-lethal dose LD50 4468 mg / kg for male / female rats

Dermal

Half-lethal dose LD50 for rats over 2000 mg / kg

Inhalation

The semi-lethal concentration of LC50 is more than 2.3 mg / I when exposed to the whole body for 4 hours.

Irritation

Skin

Irritating to skin. Prolonged or repeated skin contact with clothing soaked in the material may cause dermatitis. Symptoms may include redness, rash, swelling, dryness, and cracking of the skin.

Eyes

Eye irritation possible. Results are based on data from components or similar products.

Airways

If the material smokes or emits vapors when heated, their influence may cause some irritation of the mucous membranes and upper respiratory tract. Results are based on data from components or similar products.

Sensitivity increase

Skin

There is no evidence that the product or its components cause skin sensitization.

Airways

There is no data to indicate that the product or its components may be respiratory sensitizers. **Eves**

There is no evidence that the product or its components cause sensitization of the eyes.

Chronic toxicity

NOEL визначено як 160 мг/кг/день, і NOAEL для системної токсичності 40 мг/кг/день для щурів

Carcinogenicity No data available

Mutagenicity No data available

Reproductive toxicity No data available

Other information Other health threats are unknown

SECTION 12: Environmental Safety

12.1 Toxicity Freashwater fish

The acute semi-lethal concentration of LC₅₀ exceeds 1000 mg / L. Results are based on data from components or similar products.

Freshwater spineless

The acute semi-lethal EC50 concentration is 100 - 1000 mg / I. Chronic effect at a concentration of 1 - 10 mg / I.

Motor Oil DIESEL SAE 30

Printed: 09.03.2021 vesion 1.0

Internal Product Code: 20533

page 8 of 9

Results are based on data from components or similar products.

Seaweed

The acute semi-lethal EC50 concentration is 10 - 100 mg / I. Results are based on data from components or similar products.

Sea fish

No determination was made.

Marine spineless

No determination was made.

Bacteria

No determination was made.

12.2 Persistence and tendency to degradation

Difficult to biodegrade. Results are based on data from components or similar products.

12.3 Bioaccumulation potential

Unspecified

12.4 Mobility in soil

Due to its reduced water solubility, the product is mainly separated mechanically in biological treatment plants. Results are based on data from components or similar products.

12.5 Result of PBT and vPvB assessment

Absent

12.6 Other side effects

Unknown

SECTION 13: Disposal recommendations

13.1 Waste treatment methods Recommendation

Cannot be disposed of with household waste. Do not allow to enter sewers and waterways.

Waste (unused products)

Waste oils and waste liquid fuels; Waste from the engine, gearbox, mineral based lubricants from the engine, gearbox, grease are hazardous waste.

Disposal of uncleaned packaging and recommended cleaning products

Packaging that cannot be cleaned must be recycled. Dispose of in accordance with official regulations.

SECTION 14: Transport safety requirements

14.1 UN Number ADR/RID not regulated ICAO not regulated IMDG not regulated

14.2 UN exact shipping name

ADR/RID not regulated ICAO not regulated IMDG not regulated

14.3 Hazard classes of goods being transported

ADR/RID not regulated ICAO not regulated IMDG not regulated

14.4 Packaging ADR/RID not regulated ICAO not regulated IMDG not regulated

14.5 Harmful impact on the environment ADR/RID not regulated

Motor Oil DIESEL SAE 30

Printed: 09.03.2021 vesion 1.0

Internal Product Code: 20533

ICAO not regulated IMDG not regulated

14.6 Special precautions for users

Check eligibility before transporting material at elevated temperatures.

14.7 Transportation in bulk is carried out in accordance with Appendix II of the International Convention for the Prevention of Water Pollution 73/78 and IBC standards

Unspecified

SECTION 15: Regulatory information

15.1 Regulatory provisions concerning the safety, health and environment of the middle / legislation Global Chemical Inventories

Australia	All components are in accordance with the Australian Chemical Designation Requirements.
Canada	All components are in accordance with the Canadian Environmental Protection Act and are on the List of Substances Permitted for Import.
China	All components of this product are listed on the China Existing Chemicals List.
EU	For more information on the compliance of this product with the REACH directive, please
	send your request to the address provided in section 1.
Japan	All components are in compliance with Japan Chemicals Control Law.
Korea	All components are in accordance with Korean regulations.
New Zealand	All components meet New Zealand chemical requirements.
The Philippines	All components are in compliance with the Philippine Toxic and Hazardous Substances and Nuclear Waste Control Act 1969 (R.A. 6969).
Switzerland	All components are in accordance with the Swiss List of Substances Hazardous to the Environment.
The USA	All components of this material are TSCA compliant or uncontrolled.

Water safety classes in Germany

Water pollution class WGK = 2 in accordance with the Aquatic Hazard Directive, VwVwS, dated 17 May 1999.

15. 2 Chemical restrictions

Chemical safety assessment has not been carried out.

SECTION 16: Other information

Created

Chief Technologist Department of LLC JV YUKOIL Date of creation 05/03/2021 Risk guidelines (R Phrases) R36 - Irritating to eyes

R38 - Irritating to eyes R41 - Risk of serious damage to eyes R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Important Risk Statements

H315 - Causes skin irritation H318 - Causes serious eye damage H319 - Causes serious eye irritation H411 - Toxic to aquatic life with long lasting effects

Additional information

The above data applies only to the specified product, but they become invalid if the product is used in conjunction with other materials or processed. The data correspond to our current state of knowledge and experience, but they do not constitute a guarantee of the product quality, but only serve to describe the product and do not form the basis of the contractual relationship. Applicable laws and regulations must be respected by the recipient of our products at their own risk. (Data for Hazardous Ingredients was taken from the latest version of the supplier's safety data sheets.)